



No.:
REDSZ2025-0108-H

TEST REPORT


NAME OF SAMPLE : NeoEyes NE101 Sensing Camera

APPLICANT : Xiamen CamThink Technology Co., Ltd.

CLASSIFICATION OF TEST : N/A

CVC Testing Technology (Shenzhen) Co., Ltd.



Applicant	Name: Xiamen CamThink Technology Co., Ltd. Address: Building C09, Software Park Phase III, Xiamen 361024, Fujian, China		
Manufacturer	Name: Xiamen CamThink Technology Co., Ltd. Address: Building C09, Software Park Phase III, Xiamen 361024, Fujian, China		
Equipment Under Test	Product Name: NeoEyes NE101 Sensing Camera Model Name: NE101 Additional Model Name: NT101 Brand Name: CamThink Serial NO.: N/A Sample NO.: 202507115892-6		
Date of Receipt.	Jul. 14, 2025	Date of Testing	Jul. 14, 2025 ~ Aug. 06, 2025
Test Specification		Test Result	
EN IEC 62311:2020 EN 50665:2017		PASS	
Evaluation of Test Result	The equipment under test was found to comply with the requirements of the standards applied. Seal of CVC Issue Date: Aug.06,2025		
Compiled by:  Zhu Yulin Name Signature	Reviewed by:  Mo Xianbiao Name Signature	Approved by:  Dong Sanbi Name Signature	
Other Aspects: NONE.			
Abbreviations:OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



TABLE OF CONTENTS

RELEASE CONTROL RECORD4

1. GENERAL INFORMATION5

1.1 GENERAL PRODUCT INFORMATION 5

1.2 DESCRIPTION OF ACCESSORIES 5

2. RF EXPOSURE MEASUREMENT6

2.1 INTRODUCTION 6

2.2 LIMIT 6

2.3 CLASSIFICATION OF THE ASSESSMENT METHODS 6

2.4 TEST RESULTS 7



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
REDSZ2025-0108-H	Original release	Aug. 06, 2025



1. GENERAL INFORMATION

1.1 GENERAL PRODUCT INFORMATION

PRODUCT NAME	NeoEyes NE101 Sensing Camera	
BRAND NAME	CamThink	
MODEL NAME	NE101	
ADDITIONAL MODEL NAME (Remark 5)	NT101	
POWER SUPPLY	DC 6V(4*1.5V AAA battery)	
MODULATION TYPE	WiFi 2.4G	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
OPERATING FREQUENCY	WiFi 2.4G: 2412MHz ~ 2472MHz	
MAX CONDUCTED POWER	WiFi 2.4G: 19.98dBm(EIRP)	
ANTENNA GAIN (Remark 4)	PCB Antenna, with 3.26dBi gain	
I/O PORTS	Refer to User's Manual	
CABLE SUPPLIED	N/A	
Remark:		
1. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.		
3. Please refer to the EUT photo document (Reference No.: REDSZ2025-0108-EUT) for detailed product photo.		
4. Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, CVC is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.		
5. This sample only differs in model name.		

1.2 DESCRIPTION OF ACCESSORIES

N/A



2. RF EXPOSURE MEASUREMENT

2.1 INTRODUCTION

This International Standard applies to electronic and electrical equipment for which no dedicated product- or product family standard regarding human exposure to electromagnetic fields applies.

The frequency range covered is 0 Hz to 300 GHz.

The object of this generic standard is to provide assessment methods and criteria to evaluate such equipment against basic restrictions or reference levels on exposure of the general public related to electric, magnetic and electromagnetic fields and induced and contact current.

2.2 LIMIT

According to EN 62311: 2020, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation

FREQUENCY RANGE	E-FIELD STRENGTH (V/m)
10MHz-400MHz	26
400MHz-2000MHz	$1.375 f^{1/2}$
2GHz-300GHz	61

NOTE: F is operating frequency in MHz

2.3 CLASSIFICATION OF THE ASSESSMENT METHODS

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the wireless easy install sheet. So, this product under normal use is located on electromagnetic far field between the human body.

Far Field Calculation Formula

$$E = \eta_0 H = \frac{\sqrt{30PG(\theta, \phi)}}{r}$$

G = antenna gain relative to an isotropic antenna
 θ, ϕ = elevation and azimuth angles to point of investigation
r = distance from observation point to the antenna
 η_0 = Characteristic impedance of free space



2.4 TEST RESULTS

Mode	Frequency (MHz)	Max EIRP(dBm)	Max EIRP(mW)	E-Field Strength (V/m)	E-Field Strength Limit (V/m)	PASS / FAIL
WiFi 2.4G	2412-2472	16.72	3.26	8.64	61.00	0.020

Compliant with the RF exposure requirements.

----- End of the Report -----

检测公司章



Important

- (1) The test report is invalid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of tester, reviewer and approver;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days;
- (6) Generally, commission test results apply to the samples as received. The sample information is provided by the customer and laboratory is not responsible for its authenticity;
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

Address: No. 1301-14&16, Guanguang Road, Xinlan Community, Guanlan Subdistrict, Longhua District, Shenzhen, Guangdong, China

Post Code: 518110 Tel: 0755-23763060-8805

Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn